

# Conex | Bänninger

# Series 5000

Медни капилярни фитинги за запояване



Характеристики и предимства:

- Предлагат се с размери 15-159 mm.
- Подходящи за свързване на медни тръби в съответствие с EN 1057.

Conex Серия 5000 (сребърна спойка)

Размер mm	Максимално работно налягане (bar)		
	-20° to 100°C	150°C	200°C
15	35.1	29.8	15.8
18	33.3	28.3	15.0
22	30.6	26.0	13.8
28	23.8	20.3	10.7
35	21.1	17.9	9.5
42	19.3	16.4	8.7
54	16.3	13.9	7.3
66.7	15.4	13.1	6.9
76.1	15.4	13.1	6.9
108	14.2	12.1	6.4
133	10.6	7.7	4.1
159	11.8	8.6	4.6

Conex | Bänninger  
**Series 5000**

Медни капилярни фитинги за запояване

Straight Coupler



**5270**  
 From: 15mm  
 To: 159mm

Male Straight Connector



**4243G**  
 From: 15 x 1/2"  
 To: 108 x 4"

Fitting Reducer



**5243**  
 From: 22 x 15mm  
 To: 159 x 108mm

Elbow



**5090**  
 From: 15mm  
 To: 159mm

45° Elbow



**5301**  
 From: 15mm  
 To: 159mm

Tee - Equal



**5130**  
 From: 15mm  
 To: 159mm

Tee - Reduced Branch



**5130**  
 From: 22 x 22 x 15mm  
 To: 159 x 159 x 108mm

End Cap



**5301**  
 From: 15mm  
 To: 159mm

Female Straight Connector



**4270G**  
 From: 15 x 1/2"  
 To: 54 x 2"



\*Conex|Bänninger products are approved by numerous Standards Authorities and Certification Bodies. For more details on this product range, please email our technical team at: [technical@ibpgroup.com](mailto:technical@ibpgroup.com).

**Conex Universal Limited:** Global House, 95 Vantage Point, The Pensnett Estate, Kingswinford, West Midlands DY6 7FT, UNITED KINGDOM.  
 Tel: +44 (0)121 557 2831 | Fax: +44 (0)121 520 8778 | Email: [salesuk@ibpgroup.co.uk](mailto:salesuk@ibpgroup.co.uk) | Website: [www.ibpgroup.com](http://www.ibpgroup.com)